JAOD3090 Air Operated Waste Oil Drainers

Solution for Lubricating Equipment
LubeWORKS™

Designed to drain, by gravity, waste oil from engines, gear boxes and differentials of all vehicles. The emptying of the drained oil inside the reservoir is air operated.



Warning: Do not use with corrosive or inflammable products

FEATURES:

- Air operated oil drainer with centre mounted adjustable collecting bowl
- Adjustable collecting bowl height to work with jack, lift or servicing cock
- Equipped with a valve for collecting bowl to inspect drained oil before it enters the reservoir
- Can be equipped with a special support to allow filters to drain

TECHNICAL DATA

Tank capacity (litre/gallon):	90/24
Collection bowl capacity (litre/gallon):	18/4.75
Collection bowl size (mm/inch):	400x190/16x8
Maximum height (mm/inch):	1150/45
Minimum height (mm/inch):	1850/72
Hose length (m/inch):	2/79
Air pressure for empties (bar/psi):	1/14
Tank size (mm/inch):	406x780/16x31
Unit dimensions (mm/inch):	630x415x1160/25x15x45
G.W. (kgs/lbs):	32/70.5 empty
Packing volume (cbm/cft):	0.28x10
Collection bowl packing (cbm/cft):	0.02/0.7

2 YEAR WARRANTY 2 WARRANTY

For up to date information and prices please visit - www.redashe.com